

100 Royal Way Temple, GA 30179 Phone (800) 520-6593

SPECIFICATION DATA SHEET

Date: 7/1/2014

MODEL No. 101 **Snaplock Furnace Pipe**

DIMENSIONAL DATA

SIZES AVAILABLE: 3" THROUGH 24" DIAMETER

FABRICATION DATA

Material:

ASTM-A653 CS Type B Galvanized Steel, G-30 Coating LFQ Chemical Treatment

*26GA G-90 Coating LFQ Chemical Treatment Available to meet SMACNA

Diameter	Length Available	Gauges Available
3"	2', 5'	30, 28, 26
4"	2', 4', 5'	30, 28, 26, 24
5"	2', 4', 5', 10'	30, 28, 26, 24
6"	2', 4', 5', 10'	30, 28, 26, 24
7"	2', 4', 5', 10'	30, 28, 26, 24
8"	2', 4', 5', 10'	30, 28, 26, 24
9"	2', 4', 5'	30, 28, 26, 24
10"	2', 4', 5'	30, 28, 26, 24
12"	2', 4', 5'	30, 28, 26, 24
14"	2', 3', 4', 5'	28, 26, 24
16"	2', 3', 4', 5'	28, 26, 24
18"	2', 3', 4', 5'	26, 24
20"	2', 3', 4', 5'	26, 24
22"	2', 3', 4', 5'	26, 24
24"	2', 3', 4'	24

FEATURES

Male and Female Locks are roll formed using a Modified Reeves Design. Pipe has 3/8" stiffener beads Rolled every 12" for added rigidity. 2" Water Gauge +/-

OPTIONS

Aluminum: 4-14"-Fabricated from 3003-H14 in 26GA Stainless Steel: 4-14"-Fabricated from T304 2B in 26GA Both Stainless and Aluminum are sold in 4' pieces.

24GA Matte Black available

