

100 Royal Way Temple, GA 30179 Phone (800) 520-6593

SPECIFICATION DATA SHEET

Date: 11-10-14

MODEL No. 440

Vertical 90deg Elbow for Rectangular Duct & Wall Stack

1 21	ON	٩L	DΡ	١IA
_				

For Wall Stack:			For Rectangular Duct			
<u>B</u>	<u>C</u>	<u>A</u>	<u>B</u>	<u>C</u>		
8	5 1/4	8, 10	10	8" = 12 1/4"		
10	5 1/4	8, 10	12	10" = 14 1/4		
12	5 1/4	8, 10	14			
14	5 1/4	8, 10	16			
		8, 10	18			
		8, 10	20			
		8, 10	22			
		8, 10	24			
		8, 10	26			
		8, 10	28			
		8, 10	30			
	<u>B</u> 8 10 12	<u>B</u> <u>C</u> 8 5 1/4 10 5 1/4 12 5 1/4	B C A 8 5 1/4 8, 10 10 5 1/4 8, 10 12 5 1/4 8, 10 14 5 1/4 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10 8, 10	B C A B 8 5 1/4 8, 10 10 10 5 1/4 8, 10 12 12 5 1/4 8, 10 14 14 5 1/4 8, 10 16 8, 10 18 8, 10 20 8, 10 22 8, 10 24 8, 10 26 8, 10 28		

FABRICATION DATA

Material:

ASTM-A653 CS Type B Galvanized Steel, G-30 Coating LFQ Chemical Treatment

Standard Gauge: 26GA

Assembly:

The elbows are assembled by using a roll formed hammer lock to secure the back and throat.

FEATURES

S-locks and drives are included with all rectangular duct

S-lock rails are roll formed on to secure wall stack to the elbow during installation

OPTIONS

Additional Sizes Available for Rectangular Duct

