

100 Royal Way Temple, GA 30179 Phone (800) 520-6593

SPECIFICATION DATA SHEET

Date:11/11/18

MODEL(s) 800, 801, 802, 803 MODEL(s) 800G, 801G, 802G, 803G Conical Spin Fittings for Metal

DIMENTIONAL DATA

AxB	С	С
Diameter	Height	Height w/damper
6 x 4	10"	10"
7 x 5	10"	10"
8 x 6	10"	10"
9 x 7	10"	10"
10 x 8	10"	10"
12 x 9	10"	10"
12 x 10	10"	10"
14 x 12	10"	10"
16 x 14	10"	10"
18 x 16	10"	10"
20 x 18	10"	10"

FABRICATION DATA

Material:

ASTM-A653 CS Type B Galvanized Steel G-30 Coating LFQ Chemical Treatment 4" through 18" - 24GA

Assembly:

Continuous weld longitudinal seam for no air leakage.

Meets SMACNA Gauge Standards - 10" W.G. Static Pressure

Available Options

Gasket: Fire Retardant Polyethylene Foam with

Double Stick 3M Tape UL94 HF-1

Damper: Standard Regulator or Raised Quadrant

Raised Quadrant: Rossi TwistKnob

Standoff Regulator for 2" wrap

Scoop: Available to aid in air flow

Conical Spin Fittings Model(s) 800, 801, 802, 803


(shown with Damper and Standard Regulator)

Model Options

Model 800: Spin-in Conical

Model 801: Spin-in Conical with Scoop Model 802: Spin-in Conical with Damper Model 803: Spin-in Conical with Scoop

and Standard Regulator Damper



Conical Fittings with Airtite Gasket Model(s) 800G, 801G, 802G, 803G, 803GRQ

(shown with Gasketed Flange, Scoop, Damper and Raised Quadrant)

